



Mini Palla Round In-Out 1 Trimless RE63-K40D30

Palla Round In-Out



Ø162



Round Adjustable Trimless recessed mounted downlight with LED

- Light head: Retractable, 350° rotatable, 30° Inward or 60° Outward tilting.
- Made from die cast aluminium in powder coat finish, light head designed with integrated heat-sink.
- Optical grade metalized polycarbonate reflector.
- Hot-aim, self-locking, tool-free adjustment.
- Safety cable included.
- Passive cooling COB LED source 4000K CRI>80 of 2650 nominal lumen.
- System power 26W; System efficacy 91,3 lm/W; 2375 delivered lumen.
- Optic: reflector beam angle: 30°.
- Supplied with spill ring device for minimal glare and smooth light effect.
- Supplied with non-dimming driver positioned remotely 220-240V 50/60Hz.
- Dimming options available on request.
- Design by Franco Mirezzi.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
RE63	10 - Black 11 - White	K40-4000K	>80	D30-30°	1-10V DC Dali Phase PWM LaserDim	0 1 2 3 5

Ordering code example : RE63 - K40 D30