




## Micro Palla Round In-Out 1 Trim

## RE59-K30D18

Palla Round In-Out



### Round Adjustable Trim recessed mounted downlight with LED

- Light head: Retractable, 350° rotatable, 30° Inward or 60° Outward tilting.
- Made from die cast aluminium in powder coat finish, light head designed with integrated heat-sink.
- Optical grade metalized polycarbonate reflector.
- Hot-aim, self-locking, tool-free adjustment.
- Safety cable included.
- Passive cooling COB LED source 3000K CRI>80 of 1460 nominal lumen.
- System power 16W; System efficacy 73,3 lm/W; 1172 delivered lumen.
- Optic: reflector beam angle: 18°.
- Supplied with spill ring device for minimal glare and smooth light effect.
- Supplied with non-dimming driver positioned remotely 220-240V 50/60Hz.
- Dimming options available on request.
- Trimless version is available.
- Design by Franco Mirezni.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

### Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
RE59	10 - Black 11 - White	<b>K30-3000K</b>	>80	<b>D18-18°</b>	1-10V DC	0
					Dali	1
					Phase	2
					PWM	3
					LaserDIM	5

Ordering code example : RE59 -    K30 D18