



Mini Palla Round In-Out 2 Trimless RE69-K40D60

Palla Round In-Out



307x162



Round Adjustable Trimless recessed mounted downlight with LED

- Twin Light heads: Retractable, 350° rotatable, 30° Inward or 60° Outward tilting.
- Made from die cast aluminium in powder coat finish, light head designed with integrated heat-sink.
- Optical grade metalized polycarbonate reflector.
- Hot-aim, self-locking, tool-free adjustment.
- Safety cable included.
- Passive cooling COB LED source 4000K CRI>80 of 2x2650 nominal lumen.
- System power 2x26W; System efficacy 91,3 lm/W; 2x2375 delivered lumen.
- Optic: reflector beam angle: 60°.
- Supplied with spill ring device for minimal glare and smooth light effect.
- Supplied with non-dimming driver positioned remotely 220-240V 50/60Hz.
- Dimming options available on request.
- Design by FrancMirensi.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

Specifications

Designed and manufactured to comply with European standard EN 60598.



| Product code | Finish | Color temperature | CRI | Beam angle | Dim. options | Code |
|--------------|--------------------------|-------------------|-----|----------------|--------------|------|
| RE69 | 10 - Black 11 - White | K40-4000K | >80 | D60-60° | 1-10V DC | 0 |
| | | | | | Dali | 1 |
| | | | | | Phase | 2 |
| | | | | | PWM | 3 |
| | | | | | LaserDIM | 5 |

Ordering code example : RE69 - __ K40 D60 __