



Micro Palla Round In-Out 2 Trim

RE65-K40D26

Palla Round In-Out



235x120



Round Adjustable Trim recessed mounted downlight with LED

- Twin Light heads: Retractable, 350° rotatable, 30° Inward or 60° Outward tilting.
- Made from die cast aluminium in powder coat finish, light head designed with integrated heat-sink.
- Optical grade metalized polycarbonate reflector.
- Hot-aim, self-locking, tool-free adjustment.
- Safety cable included.
- Passive cooling COB LED source 4000K CRI>80 of 2x1540 nominal lumen.
- System power 2x16W; System efficacy 78,1 lm/W; 2x1250 delivered lumen.
- Optic reflector beam angle: 26°
- Supplied with spill ring device for minimal glare and smooth light effect.
- Supplied with non-dimming driver positioned remotely 220-240V 50/60Hz.
- Dimming options available on request.
- Trimless version is available.
- Design by FrancMirensi.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
RE65	10 - Black 11 - White	K40-4000K	>80	D26-26°	1-10V DC	0
					Dali	1
					Phase	2
					PWM	3
					LaserDIM	5

Ordering code example : RE65 - K40 D26